

T-SHIRT

IDEA & SALES GUIDE

SEEKING THE PERFECT KEEPSAKE



**WE'VE GOT
INSPIRATIONAL
MARKETING
DOWN
TO A TEE!**

SANMAR

WANT TO TAKE YOUR BASEBALL DISPLAY TO THE NEXT LEVEL?

LET US SHOW YOU HOW!



SUPPLIES

- 2 48"X 96" FAUX BRICK PANELS
- DRILL
- STUD FINDER
- ANCHOR SCREWS
- 1" SCREWS
- 48"X 96" TURF GRASS
- OFFICIAL STANDARD BASEBALL PLATE
- 8 BASEBALLS
- VISE GRIPS
- 3/4" DRILL SPADE BIT
- 2 PIECES OF 12" PLUMBER PIPES
- 1 PIECE OF 36" PLUMBER PIPE
- 8 FLANGES
- 2 PIECES OF 2" PLUMBER PIPES
- 4 WOOD BASEBALL BATS
- 8' PVC PIPE
- CIRCULAR SAW
- YELLOW PAINT
- BASEBALL SHOES
- LARGE WOOD NUMBERS
- WHITE SPRAY PAINT
- POWER JIGSAW

HOW TO CREATE THIS DISPLAY

- 1 SECURE THE 48"X 96" FAUX BRICK PANELS TO THE WALL. SCREW THEM TO THE STUDS OR USE ANCHOR SCREWS.
- 2 PLACE THE TURF GRASS ON THE GROUND AT THE BASE OF THE DISPLAY.
- 3 PUT THE BASEBALL PLATE ON TOP OF THE TURF GRASS, FRONT AND CENTER.
- 4 ATTACH TWO BASEBALLS TO A TABLE WITH VISE GRIPS. DRILL TWO SEPARATE HOLES HALFWAY THROUGH EACH BASEBALL WITH 3/4" DRILL SPADE BIT. ENSURE THE TWO HOLES MEET UP IN THE MIDDLE OF EACH BASEBALL.
- 5 USE EACH BASEBALL AS 90-DEGREE CORNER CONNECTION PIECES BETWEEN THE 12" PIPES AND THE 36" PIPE.
- 6 ATTACH A FLANGE TO THE END OF EACH 12" PIPE.
- 7 DRILL THE FLANGES DIRECTLY INTO WALL ABOUT 4' ABOVE THE GROUND ON THE LEFT SIDE OF THE DISPLAY.
- 8 HANG CLOTHES ON THE 36" PIPE.
- 9 DRILL TWO BASEBALLS APPROXIMATELY HALFWAY THROUGH WITH 3/4" DRILL SPADE BIT.
- 10 ATTACH THE BASEBALLS TO THE END OF THE 2" PLUMBER PIPES.
- 11 ATTACH 2" PLUMBER PIPES TO FLANGES.
- 12 SECURE THESE BASEBALL FIXTURES TO THE TOP CENTER AND THE UPPER RIGHT SIDE OF THE WALL.
- 13 HANG CLOTHES ON THE 2" PIPES.
- 14 ATTACH BASEBALL BATS TO THE WALL USING SCREWS AND FOUR FLANGES. BATS SHOULD BE IN A ROW, POINTED DOWNWARD, ABOUT 4' FROM THE GROUND ON THE RIGHT SIDE OF THE DISPLAY.
- 15 SECURE THE PVC PIPE TO A TABLE AND USE THE CIRCULAR SAW TO CUT IT IN HALF LENGTH-WISE. SPRAY PAINT ONE HALF YELLOW.
- 16 ONCE DRY, USE SCREWS TO ATTACH THE PVC PIPE ALONG THE TOP EDGE OF THE WALL, LIKE A TRIM.
- 17 DRILL HOLE APPROXIMATELY HALFWAY INTO FOUR BASEBALLS WITH 3/4" DRILL SPADE BIT.
- 18 HANG TWO BASEBALLS ON SCREWS NEAR THE TOP LEFT SECTION OF THE WALL, AND TWO IN THE RIGHT CENTER SECTION OF THE WALL.
- 19 DRILL A SCREW INTO THE WALL ABOUT 2' FROM THE GROUND ON THE LOWER RIGHT SIDE OF THE WALL. LEAVE SPACE BETWEEN THE FLAT END OF THE SCREW AND THE WALL.
- 20 TIE THE BASEBALL SHOELACES TOGETHER AND HANG THEM FROM THE SINGLE SCREW.
- 21 SPRAY PAINT THE WOOD NUMBERS WHITE.
- 22 ATTACH EACH NUMBER TO THE TOP RIGHT PORTION OF THE WALL.

TIPS ✓ PURCHASE THE WOOD NUMBERS ONLINE OR CUT THEM OUT WITH A POWER JIGSAW.

✓ IF USING A POWER JIGSAW TO CUT OUT THE NUMBERS, DRAW THE NUMBERS ON THE WOOD FIRST.